

1



Introducing the Ecotextures® Flooring collection, a unique and sustainable flooring option crafted from OSB (oriented strand board) products with **coordinating wood panels available**. This rapidly renewable timber is extremely durable and does not require the use of urea-formaldehydes. Ecotextures® Flooring is component lumber that is SFI (Sustainable Forestry Initiative) certified and meets requirements of AF & PA (American Forest and Paper Association) and CSA (Canadian Standards Association). Please note that variations in color and texture may occur due to the nature of the material. For updates and complete collection offerings and specifications, please visit www.archsystems.com.



Steel
FLCPI003



Natural
FLCPI004



Wenge
FLCPI007




Chocolate
FLCPI008



Gray
FLCPI009



Olive
FLCPI010



Rust
FLCPI011

Specifications

- **Thickness:**
13.8 mm standard
- **Width:**
6.14" standard
- **Length:**
47.1" standard
- **Construction:**
Engineered 5 ply, 2.9 mm wear layer (PSI rating 1058) tongue and groove, micro bevel 4 sides
- **Finish:**
Commercial ceramic urethane
- **Color:**
7 standard, custom colors available
- **Species:**
Aspen, all stranded and highly compressed under proprietary manufacturing to expose only edge grain and is stronger and more predictable than conventional "solid wood"
- **LEED®:**
Can contribute to LEED® MR Credit 6: Rapidly Renewable Materials, MR Credit 7: Certified Wood (pending), EQ Credit 4: Low-Emitting Materials



ARCHITECTURAL SYSTEMS, INC.

Tel: 800.793.0224 • Fax: 800.793.0225 • sales@archsystems.com

www.archsystems.com